



#505 PUDDLE PLASTER

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION:

Elastek® #505 Puddle Plaster is a lightweight, trowel-grade, black reinforced filler used to eliminate or reduce small ponds of water. Reinforcing fiberglass fibers strengthen the coating, and allow for thicker applications. Once cured and top coated, Puddle Plaster is firm, durable, and will not re-emulsify in ponding water.

TYPICAL USES:

Puddle Plaster can be used in scupper areas, around drains and valleys, and in low areas expected to trap water. It will not re-emulsify in ponding water. Once cured and top-coated, this emulsion is firm, durable, and flexible. *Puddle Plaster* is not elastomeric. *Puddle Plaster* should be coated with E-las-tek® #500 Sealer Emulsion or an E-las-tek® topcoat to fill any pinholes and to protect from sun damage.

- Usually will not discolor white topcoat
- May be used over most existing asphalt roofing
- May become soft in hot weather unless top coated with a reflective coating
- May be used on asphalt built-up, granulated, modified bitumen, and metal roofs

SURFACE PREPARATION:

- *Puddle Plaster* is filler, not a patching material. Always repair leaks before applying.
- All surfaces must be thoroughly cleaned to remove oils, gravel, granules, loose coating, chalk, dirt, rust, corrosion, efflorescence, bond-breakers, and mildew to assure coating adhesion.
- Rust/corrosion must be removed, followed by a coat of commercial rust-preventive primer.
- Surfaces affording poor adhesion should be pre-coated with E-las-tek® #500 Sealer Emulsion.

APPLICATION:

Apply only in good weather when ambient temperatures exceed 50°F and no rain, dew, or frost is expected for 48 hours. Direct sun speeds drying.

- Apply with trowel or straight-edged tool at rate not to exceed ½ inch per coat.
- Material is very thick and will require smoothing.
- Dampen trowel to reduce sticking; smooth surface.
- Use E-las-tek® #500 Sealer Emulsion or topcoat to smooth and seal surface when dry.
- To avoid softening and damage from sun exposure, Puddle Plaster must be covered with two coats of a reflective topcoat.

- Before applying reflective topcoat, allow Puddle Plaster to cure a minimum of 7 days, rinse off surface oils with clean water, and allow to dry thoroughly. This improves topcoat adhesion and reduces asphalt bleed-through.
- **Solids by volume exceed 50%.**
VOC Content < 1 g/l

APPLICATION LIMITATIONS:

Normally, it is not necessary or practical to eliminate all water ponding. Reducing the size and depth of a pond reduces the time standing water remains on the roof.

- Puddle Plaster is intended for addressing localized ponding. Larger drainage problems should be referred to a qualified roofing contractor for immediate correction.
- While Puddle Plaster retains some flexibility, it is not elastomeric.
- Do not apply at temperatures below 50°F (10°C).
- Not for use on foam or gravel roofs
- Call ITW POLYMERS SEALANTS NORTH AMERICA before applying to single-ply roofs.

COVERAGE:

5 gallons will cover an area approximately 4 ft x 4 ft area, 1/2 inch-deep wet. (16 square feet)
Material will dry to about 3/8 inch. *Puddle Plaster* is not intended to cover large areas.

STORAGE:

Keep Puddle Plaster containers tightly sealed and protected against high temperatures. This product will freeze and should not be stored below 35°F (2°C).
Storage beyond six months may cause the product to thicken. In such cases, the product should be diluted with clean potable water at a rate not to exceed one part water to six parts coating (1:6). Dilute slowly and mix thoroughly, adding only enough water to permit application at the proper coverage rate. Mechanical mixing is highly recommended. The product should NOT be diluted beyond the maximum dilution rate of 1:6 as this will affect product performance.

SHELF STABILITY: 6 months

SAFETY:

Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wear protective goggles, gloves, and clothing. Avoid prolonged breathing of vapors. Use with adequate ventilation. Do not take internally. Store and use away from heat. Close container tightly after each use. Do not transfer to unlabeled or breakable containers. Use only for purposes intended. **KEEP OUT OF REACH OF CHILDREN.**

ITW POLYMERS SEALANTS NORTH AMERICA, INC.

111 S. Nursery Road, Irving, TX 75060
Tel: 972-438-9111 Fax: 972-554-3939 www.itwsealants.com

8/11/2015

EFFECTS OF OVEREXPOSURE:

Contact with eyes or prolonged or repeated contact with skin can cause irritation and inflammation. Prolonged breathing of vapors can cause respiratory difficulty, dizziness, headache, nausea, irritation of nose or throat, drowsiness, blurred vision, and coma. Ingestion can expose person to an order of oral toxicity; aspiration into lungs can cause serious injury or death.

FIRST AID PROCEDURES:

Eye Contact: Flush with water for 15 minutes. If redness persists, seek medical attention immediately.

Skin Contact: Wash with soap and water after wiping off excess material.

If irritation persists, seek medical attention.

Inhalation: Remove to fresh air. If breathing difficulty persists, give oxygen or resuscitate and SEEK MEDICAL ATTENTION IMMEDIATELY.

Ingestion: Induce vomiting. As vomiting occurs, keep head below hips to prevent aspiration. SEEK MEDICAL ATTENTION IMMEDIATELY

NOTICE TO PURCHASER:

While the information and data contained herein are presented in good faith and believed to be reliable, they do not constitute part of our terms and conditions of sales. Nothing herein shall be deemed to constitute a warranty, expressed or implied. Data provided here is based on our best knowledge at time of printing and is subject to change. Elastek offers coatings to fill or coat ponding areas and to handle difficult cult substrates. For most current information check our website: www.elastek.com; or contact us at info@itwsealants.com or 877-352-7835.

EXCLUSION OF WARRANTIES:

AS TO THE HEREIN DESCRIBED MATERIALS, ITW POLYMERS SEALANTS NORTH AMERICA, INC. MAKES NO WARRANTIES WHETHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SINCE THE USE OF THE HEREIN DESCRIBED MATERIALS INVOLVES MANY VARIABLES IN METHODS OF APPLICATION, HANDLING AND/OR USE, THE USER IN ACCEPTING AND USING THESE MATERIALS ASSUMES ALL RESPONSIBILITY FOR THE END RESULT. THE PURCHASE OF THIS ITW POLYMERS SEALANTS NORTH AMERICA, INC. PRODUCT IS SUBJECT TO THE TERMS AND CONDITIONS OF AN "AS IS" SALE, AND IF THE PRODUCT IS PROVED TO BE DEFECTIVE, THE EXCLUSIVE REMEDY, AT ITW POLYMERS SEALANTS NORTH AMERICA, INC.'S OPTION, SHALL BE TO REPLACE THE DEFECTIVE ITW POLYMERS SEALANTS NORTH AMERICA, INC. PRODUCT. ITW POLYMERS SEALANTS NORTH AMERICA, INC. SHALL NOT OTHERWISE BE LIABLE FOR LOSS OF DAMAGES, WHETHER DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL, REGARDLESS OF THE LEGAL THEORY ASSERTED, INCLUDING NEGLIGENCE, WARRANTY OR STRICT LIABILITY.

Complete technical information is available from
ITW Polymers Sealants North America, Inc.