

# SAFETY DATA SHEET

Date Prepared : 09/13/2017  
 MSDS No : EG-C-1000FR  
 Date Revised : 09/13/2017  
 Revision No : 14

## E-LAS-TEK #120 Solar Tek Extreme PLUS

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** E-LAS-TEK #120 Solar Tek Extreme PLUS

**MANUFACTURER**

ITW Polymers Sealants North America  
 3700 S Palo Verde Rd.  
 Tucson, AZ 85713

**24 HR. EMERGENCY TELEPHONE NUMBERS**

CHEMTREC (US Transportation): (800) 424-9300

**COMMENTS:** E-LAS-TEK is a registered trademark of Illinois Tool Works, Inc.

### 2. HAZARDS IDENTIFICATION

**GHS CLASSIFICATIONS**

**Health:**

Target Organ Toxicity (Repeated exposure), Category 2

**GHS LABEL**



Health  
hazard

**SIGNAL WORD:** WARNING

**HAZARD STATEMENTS**

H373: May cause damage to organs through prolonged or repeated exposure.

**PRECAUTIONARY STATEMENT(S)**

**General:**

6019NUEC: Exposure may aggravate pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes.

**Prevention:**

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

**Response:**

P314: Get medical advice/attention if you feel unwell.

**Disposal:**

P501: Dispose of contents/container according to local, regional, national, and international regulations.

**EMERGENCY OVERVIEW**

**PHYSICAL APPEARANCE:** Milky liquid with an ammonia odor

**IMMEDIATE CONCERNS:** CAUTION! May cause eye, skin, nose and throat irritation.

**POTENTIAL HEALTH EFFECTS**

**EYES:** Contact may cause eye irritation.

**SKIN:** Prolonged or repeated skin contact may cause irritation.

**INGESTION:** Not likely route of entry. Harmful if swallowed, may cause nausea. Consult a physician.

# SAFETY DATA SHEET

**Date Prepared :** 09/13/2017  
**MSDS No :** EG-C-1000FR  
**Date Revised :** 09/13/2017  
**Revision No :** 14

## E-LAS-TEK #120 Solar Tek Extreme PLUS

**INHALATION:** Trace components and residual vapors may be irritating to the eyes, skin, mucous membrane, respiratory tract, and may produce symptoms of headaches and nausea in poorly ventilated areas.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Acrylic Polymer	< 50	Mixture
Aluminum Hydroxide	< 10	21645-51-2
Titanium Dioxide	< 7	13463-67-7
Ethylene Glycol	< 1.5	107-21-1
Ammonia	< 0.1	7664-41-7

### 4. FIRST AID MEASURES

**EYES:** Flush eye with tempered water for 15 minutes lifting upper and lower eye lids occasionally. If irritation persists, contact a physician.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash or dispose of clothing before reuse.

**INGESTION:** Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. Never give anything by mouth to an unconscious person.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**EYES:** Causes eye irritation.

**SKIN:** Mild to moderate skin irritant.

**INGESTION:** Single dose toxicity low to moderate.

**INHALATION:** Prolonged or excessive inhalation may cause respiratory tract irritation.

### 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** Not Applicable

**EXTINGUISHING MEDIA:** Water spray, carbon dioxide, dry chemical or foam.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon Monoxide, Carbon Dioxide, Acrylic Monomers

**EXPLOSION HAZARDS:** No known unusual hazards in a fire/explosion situation.

**FIRE FIGHTING PROCEDURES:** As in any fire, wear self-contained breathing apparatus with pressure-demand, full face piece SCBA (MSHA/NIOSH approved or equivalent) and full protective gear.

**COMMENTS:** Use water spray to cool containers exposed to fire.

### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed

# SAFETY DATA SHEET

**Date Prepared :** 09/13/2017  
**MSDS No :** EG-C-1000FR  
**Date Revised :** 09/13/2017  
**Revision No :** 14

## E-LAS-TEK #120 Solar Tek Extreme PLUS

containers for disposal. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the appropriate personal protective equipment (PPE) should participate in spill response and clean-up.

**LARGE SPILL:** Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Know and prepare for spill response before using or handling this product. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled containers for disposal. Use appropriate PPE. Place absorbent diking materials in covered containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

### 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption.

**HANDLING:** Do not handle material near food, feed or drinking water. Agitate containers before use. Keep from freezing. Keep out of reach of children.

**STORAGE:** The minimum recommended storage temperature for this material is 1 C/34 F. The maximum recommended storage temperature is 60 C/140 F. Keep from freezing; material may coagulate. Do not store this material near food, feed or drinking water.

**STORAGE TEMPERATURE:** 4.4°C (40°F) Minimum to 29.4°C (85°F) Maximum

**SHELF LIFE:** 1 year from manufacture date

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

# SAFETY DATA SHEET

**Date Prepared :** 09/13/2017  
**MSDS No :** EG-C-1000FR  
**Date Revised :** 09/13/2017  
**Revision No :** 14

## E-LAS-TEK #120 Solar Tek Extreme PLUS

### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
EXPOSURE LIMITS				
Chemical Name	Type		ppm	mg/m <sup>3</sup>
Acrylic Polymer	OSHA PEL	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
Aluminum Hydroxide	OSHA PEL	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
Titanium Dioxide	OSHA PEL	TWA	NL [1]	15 T [1]
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	NL [1]	10 [1]
		STEL	NL [1]	NL [1]
Ethylene Glycol	OSHA PEL	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	NL [1]	NL [1]
		STEL	100-C [2]	NL [2]
Ammonia	OSHA PEL	TWA	50 ppm [3]	NL [3]
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	25 ppm	NL
		STEL	35 ppm	NL

**Footnotes:**

1. NL = Not Listed
2. C = Ceiling
3. OSHA limits per 29 CFR 1910.1000 Table Z-1 & Z-2

**ENGINEERING CONTROLS:** Exterior-use product. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

**PERSONAL PROTECTIVE EQUIPMENT**

**EYES AND FACE:** Wear safety glasses with side shields, goggles or full-face shield as required by 29 CFR 1910.133 - OSHA Eye and Face Protection Standard. A suitable emergency eye wash station and safety shower should be located near the work station.

**SKIN:** Wear chemical protective clothing & boots to prevent repeated or prolonged skin contact. Wear

# SAFETY DATA SHEET

**Date Prepared :** 09/13/2017  
**MSDS No :** EG-C-1000FR  
**Date Revised :** 09/13/2017  
**Revision No :** 14

## E-LAS-TEK #120 Solar Tek Extreme PLUS

impervious gloves, if needed, to prevent repeated or prolonged skin contact.

**RESPIRATORY:** Where vapor concentrations exceed or are likely to exceed the occupational exposure limits, a NIOSH approved continuous flow supplied air respirator, hood or helmet is recommended. A NIOSH approved self-contained positive pressure breathing apparatus with full face piece is required for spills and/or emergencies.

**WORK HYGIENIC PRACTICES:** Use good hygiene practices when handling this material. Wash hands thoroughly after use.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Liquid

**ODOR:** Ammonia Odor

**COLOR:** Bright White or Energy Tan

**pH:** 9.0 to 10.5

**PERCENT VOLATILE:** 33.7

**FLASHPOINT AND METHOD:** Not Applicable

**FLAMMABLE LIMITS:** NA

**AUTOIGNITION TEMPERATURE:** Not Applicable

**VAPOR DENSITY:** > 1 (Air=1)

**BOILING POINT:** Variable F

**FREEZING POINT:** Variable F

**MELTING POINT:** Variable F

**POUR POINT:** Not Determined

**SOLUBILITY IN WATER:** Miscible

**PARTITION COEFFICIENT: N-OCTANOL/WATER:** Not Determined

**EVAPORATION RATE:** < 1

**DENSITY:** 11.6 lbs/gal

**PARTICLE SIZE:** Not Determined

**SPECIFIC GRAVITY:** 1.395

**VISCOSITY #1:** 17000 to 25000 cps

**MOLECULAR WEIGHT:** Not Determined

**(VOC):** 26.4 gr/L EPA Method 24 VOC

**OXIDIZING PROPERTIES:** Not Determined

### 10. STABILITY AND REACTIVITY

**REACTIVITY:** Yes

**HAZARDOUS POLYMERIZATION:** Product will not undergo polymerization.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition may yield the following: carbon monoxide, carbon dioxide, acrylic monomers.

# SAFETY DATA SHEET

Date Prepared : 09/13/2017  
 MSDS No : EG-C-1000FR  
 Date Revised : 09/13/2017  
 Revision No : 14

## E-LAS-TEK #120 Solar Tek Extreme PLUS

**INCOMPATIBLE MATERIALS:** There are no known materials that are incompatible with this product.

### 11. TOXICOLOGICAL INFORMATION

#### ACUTE TOXICITY

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
Acrylic Polymer	No data	No data	No data
Aluminum Hydroxide	No data	No data	No data
Titanium Dioxide	No data	No data	No data
Ethylene Glycol	6140 mg/kg	10600 mg/kg	No data
Ammonia	350 mg/kg	No data	7338 ppm (1-hr dose)

**SERIOUS EYE DAMAGE/IRRITATION:** Mild to moderate eyes and skin irritation.

#### CARCINOGENICITY

Chemical Name	IARC Status
Titanium Dioxide	2B

### 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** No environmental information was found for this product.

**ECOTOXICOLOGICAL INFORMATION:** No ecotoxicity data was found for this product.

**BIOACCUMULATION/ACCUMULATION:** No information for bioaccumulation is available.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Consult with your state and local hazardous waste requirements or guidelines to ensure compliance. Arrange disposal in accordance with EPA, state and local requirements.

### 14. TRANSPORT INFORMATION

#### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Not Regulated for Transport

**UN/NA NUMBER:** NA

**PACKING GROUP:** NA

#### AIR (ICAO/IATA)

**SHIPPING NAME:** Not Regulated

#### VESSEL (IMO/IMDG)

**SHIPPING NAME:** Not Regulated

### 15. REGULATORY INFORMATION

**UNITED STATES**

# SAFETY DATA SHEET

Date Prepared : 09/13/2017  
 MSDS No : EG-C-1000FR  
 Date Revised : 09/13/2017  
 Revision No : 14

## E-LAS-TEK #120 Solar Tek Extreme PLUS

### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**FIRE:** No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** No

### EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt. %	CAS
Ethylene Glycol	< 1.5	107-21-1

### CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt. %	CERCLA RQ
Ethylene Glycol	< 1.5	5,000
Ammonia	< 0.1	100 lbs.

### TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Acrylic Polymer	Mixture
Aluminum Hydroxide	21645-51-2
Titanium Dioxide	13463-67-7
Ethylene Glycol	107-21-1
Ammonia	7664-41-7

### CLEAN AIR ACT

Chemical Name	Wt. %	CAS
Ammonia	< 0.1	7664-41-7

### STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
Aluminum Hydroxide	Pennsylvania Right to Know List New Jersey Right to Know List
Ethylene Glycol	New Jersey Right to Know List Pennsylvania Right to Know List Massachusetts Toxic Use Reduction Act (TURA) Reportable Chemical

## 16. OTHER INFORMATION

Date Revised: 09/13/2017

INFORMATION CONTACT: (520) 624-6282

REVISION SUMMARY: This MSDS replaces the 09/13/2017 MSDS. Revised: **Section 1:** COMMENTS.

# SAFETY DATA SHEET


**Date Prepared :** 09/13/2017  
**MSDS No :** EG-C-1000FR  
**Date Revised :** 09/13/2017  
**Revision No :** 14

## E-LAS-TEK #120 Solar Tek Extreme PLUS

### HMIS RATING

<b>HEALTH</b>		<b>1</b>
<b>FLAMMABILITY</b>		<b>0</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>	<b>B</b>	

### NFPA CODES



**GENERAL STATEMENTS:** Keep out of reach of children  
 For professional or industrial use only

**MANUFACTURER DISCLAIMER:** This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his/her evaluation of the product's hazards and safety precautions to be taken in its use. The data in this SDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW Polymers Sealants North America. The data on this sheet relates only to the specific material designated herein. ITW Polymers Sealants North America assumes no legal responsibility for use or reliance upon these data.