

SAFETY DATA SHEET

Date Issued : 5/1/2015
MSDS No : EL500
Date Revised : 5/1/2015
Revision No : 5

E-LAS-TEK #500 Sealer Emulsion

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: E-LAS-TEK #500 Sealer Emulsion

MANUFACTURER

ITW Polymers Sealants North America
 3700 S Palo Verde Rd.
 Tucson, AZ 85713

Product Stewardship: (877) 352-7835

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300

COMMENTS: E-LAS-TEK is a registered trademark of Illinois Tool Works, Inc.

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Target Organ Toxicity (Repeated exposure), Category 2

GHS LABEL



Health
hazard

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H373: May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENT(S)

General:

6019NUEC: Exposure may aggravate pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes.

Prevention:

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

Response:

P314: Get medical advice/attention if you feel unwell.

Disposal:

P501: Dispose of contents/container according to local, regional, national, and international regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Black Paste

IMMEDIATE CONCERNS: CAUTION! May cause eye, skin, nose and throat irritation.

POTENTIAL HEALTH EFFECTS

EYES: Contact may cause eye irritation.

SKIN: Prolonged or repeated skin contact may cause irritation.

SAFETY DATA SHEET

Date Issued : 5/1/2015
MSDS No : EL500
Date Revised : 5/1/2015
Revision No : 5

E-LAS-TEK #500 Sealer Emulsion

INGESTION: Not likely route of entry. Harmful if swallowed, may cause nausea. Consult a physician.

INHALATION: Prolonged inhalation of vapor or mist can cause coughing, shortness of breath, dizziness, or intoxication.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Asphalt	< 50	8052-42-2
Bentonite Clay	< 50	1302-78-9

4. FIRST AID MEASURES

EYES: Flush eye with tempered water for 15 minutes lifting upper and lower eye lids occasionally. If irritation persists, contact a physician.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash or dispose of clothing before reuse.

INGESTION: Do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes eye irritation.

SKIN: Mild to moderate skin irritant.

INGESTION: May cause vomiting.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Not Applicable

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical or foam.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide, Carbon Dioxide

EXPLOSION HAZARDS: This material may burn, but will not readily ignite. Flammable and toxic hydrogen sulfide may form in closed headspaces. If water is applied to heated asphalt, it can cause violent foaming and boil over.

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus with pressure-demand, full face piece SCBA (MSHA/NIOSH approved or equivalent) and full protective gear.

COMMENTS: Use water spray to cool containers exposed to fire.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the appropriate personal protective equipment (PPE) should participate in spill response and clean-up.

SAFETY DATA SHEET

Date Issued : 5/1/2015
MSDS No : EL500
Date Revised : 5/1/2015
Revision No : 5

E-LAS-TEK #500 Sealer Emulsion

LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Know and prepare for spill response before using or handling this product. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled containers for disposal. Use appropriate PPE. Place absorbent diking materials in covered containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption.

HANDLING: Avoid breathing vapors. Avoid prolonged or repeated contact with skin. Remove contaminated clothing and laundry before reuse. Use adequate ventilation.

STORAGE: Keep from freezing, material may coagulate. Do not store this material near food, feed or drinking water. Keep containers closed when not in use. Do not handle or store near heat or strong oxidants. Adequate ventilation required.

STORAGE TEMPERATURE: 15.6°C (60.1°F) Minimum to 26.7°C (80.1°F) Maximum

SHELF LIFE: 6 months from manufacture date

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³
Asphalt	TWA	NL [1]	NL [1]	NL [1]	0.5 mg/m ³ [1]
	STEL	NL [1]	NL [1]	NL [1]	NL [1]
Bentonite Clay	TWA	NL [1]	0.5 mg/m ³ [1]	NL [1]	0.5 mg/m ³ [1]
	STEL	NL [1]	NL [1]	NL [1]	NL [1]
Footnotes:					
1. NL = Not Listed					

ENGINEERING CONTROLS: Exterior-use product. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields, goggles or full-face shield as required by 29 CFR 1910.133 - OSHA Eye and Face Protection Standard. A suitable emergency eye wash station and safety shower should be located near the work station.

SKIN: Wear chemical protective clothing & boots to prevent repeated or prolonged skin contact. Wear impervious gloves, if needed, to prevent repeated or prolonged skin contact.

RESPIRATORY: Where vapor concentrations exceed or are likely to exceed the occupational exposure limits, a

SAFETY DATA SHEET

Date Issued : 5/1/2015
MSDS No : EL500
Date Revised : 5/1/2015
Revision No : 5

E-LAS-TEK #500 Sealer Emulsion

NIOSH approved continuous flow supplied air respirator, hood or helmet is recommended. A NIOSH approved self-contained positive pressure breathing apparatus with full face piece is required for spills and/or emergencies.

WORK HYGIENIC PRACTICES: Use good hygiene practices when handling this material. Wash hands thoroughly after use.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Paste

ODOR: Woodsy

COLOR: Dark Brown - Black

pH: Not Determined

PERCENT VOLATILE: < 1% by weight

FLASHPOINT AND METHOD: Not Applicable

FLAMMABLE LIMITS: NA to NA

AUTOIGNITION TEMPERATURE: Not Applicable

VAPOR PRESSURE: Not Determined

VAPOR DENSITY: > 1 (Air=1)

BOILING POINT: Variable F

FREEZING POINT: Variable F

MELTING POINT: Variable F

POUR POINT: Not Determined

SOLUBILITY IN WATER: Disperses but not soluble in water

EVAPORATION RATE: < 1 (n-Butyl Acetate=1)

DENSITY: 8.53 lbs/gal

PARTICLE SIZE: Not Determined

SPECIFIC GRAVITY: 1.023

VISCOSITY: Not Determined

MOLECULAR WEIGHT: Not Determined

(VOC): < 1.000 gr/L EPA Method 24 VOC

COEFF. OIL/WATER: Not Determined

OXIDIZING PROPERTIES: Not Determined

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

POLYMERIZATION: Product will not undergo polymerization.

HAZARDOUS DECOMPOSITION PRODUCTS: Heating this product that contains asphalt may produce hydrogen sulfide.

SAFETY DATA SHEET

Date Issued : 5/1/2015
MSDS No : EL500
Date Revised : 5/1/2015
Revision No : 5

E-LAS-TEK #500 Sealer Emulsion

INCOMPATIBLE MATERIALS: May react with strong oxidizing agents, such as chlorates, nitrates, or peroxides.

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Asphalt	5001 mg/kg (rats)	2001 mg/kg (rat)	No data
Bentonite Clay	No data	No data	No data

IRRITATION: Mild to moderate eyes and skin irritation.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No environmental information was found for this product.

ECOTOXICOLOGICAL INFORMATION: No ecotoxicity data was found for this product.

BIOACCUMULATION/ACCUMULATION: No information for bioaccumulation is available.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Consult with your state and local hazardous waste requirements or guidelines to ensure compliance. Arrange disposal in accordance with EPA, state and local requirements.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not Regulated for Transport

UN/NA NUMBER: NA

PACKING GROUP: NA

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Asphalt	8052-42-2
Bentonite Clay	1302-78-9

16. OTHER INFORMATION

INFORMATION CONTACT: (520) 624-6282

SAFETY DATA SHEET

Date Issued : 5/1/2015
MSDS No : EL500
Date Revised : 5/1/2015
Revision No : 5


E-LAS-TEK #500 Sealer Emulsion

REVISION SUMMARY: This MSDS replaces the 5/1/2015 MSDS. Revised: **Section 9:** PERCENT VOLATILE.

HMIS RATING

HEALTH	*	1
FLAMMABILITY		0
PHYSICAL HAZARD		0
PERSONAL PROTECTION		B

NFPA CODES



GENERAL STATEMENTS: Keep out of reach of children
 For professional or industrial use only

MANUFACTURER DISCLAIMER: This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his/her evaluation of the product's hazards and safety precautions to be taken in its use. The data in this SDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW Polymers Sealants North America. The data on this sheet relates only to the specific material designated herein. ITW Polymers Sealants North America assumes no legal responsibility for use or reliance upon these data.